



"IF" Series Drop-Through Rotary Valve

Dimensions are approximate subject to change without notice.

MODEL	cu.ft./hour @ 1 rpm [1]	HP [2]	A	B	C	D	E	F	G	H	J	K	L	M	N (npt)	weight
IF 10	2.1	1/4	4	9	1/2	7-1/4	1-3/8	8	9-3/4	15-3/8	8	5/8	7-1/2	30 mm	3/4	154
IF 15	6	1/2	6	11	1/2	10-1/2	11-9/16	9-1/2	11-9/16	15-3/8	8	7/8	9-1/2	40 mm	1	198
IF 20	14	1/2	8	13-1/2	5/8	13-1/2	14-3/4	11-3/16	13-3/16	16	8	7/8	11-3/4	40 mm	1	287
IF 25	28	1	10	16	3/4	15-1/2	16-1/4	12-1/2	14-3/4	21	12	1	14-1/4	40 mm	1-1/2	463
IF30	48	1-1/2 - 2	12	19	3/4	18-1/2	17-1/2	13-7/8	16	21	12	1	17	45 mm	1-1/2	617
IF 35	82	1-1/2 - 2	14	21	3/4	24	19-1/4	15-3/4	18-1/4	23	12	1-1/8	18-3/4	45 mm	3	904
IF 40	125	1-1/2 - 2	16	23-1/2	1	29	21	16-3/8	18-7/8	27	16	1-1/8	21-1/4	45 mm	3	1,124
IF 45	196	2 - 3	18	25-1/4	1-5/16	30	23-3/4	19-1/8	21-7/8	27-3/8	16	1-1/4	22-3/4	55 mm	3	1,576
IF 60	330	2 - 3	24	32	1-5/16	36-1/2	28	23-1/4	27-3/8	33	20	1-3/8	29-1/2	75 mm	3	2,535

[1] Standard rotor speed 25 rpm. Speeds from 6 to 40 rpm available.
 [2] HP is typical and is based on maximum capacity.

Copyright 1998 Bush & Wilton, Inc. - All Rights Reserved

BUSH & WILTON, INC.

P.O. Box 691385 | Charlotte, NC 28227- 7024
 Tel: 704.573.6858 | Fax: 704.573.6802

<http://www.bushandwilton.com>
mail@bushandwilton.com