



"OF" Series Offset Rotary Valve

Dimensions are approximate and subject to change without notice.

MODEL	cu.ft./hour @ 1 rpm [1]	HP [2]	A	B	C	D	E	F	G	H	J	K	L	M	N (npt)	P	weight
OF 10	2.1	1/4	4	9	1/2	8-1/4	10-3/8	8	9-3/4	15-3/8	8	5/8	7-1/2	30 mm	3/4	1-1/2	154
OF 15	6	1/2	6	11	1/2	10	11-9/16	9-1/2	11-9/16	15-3/8	8	7/8	9-1/2	40 mm	1	3	198
OF 20	14	1/2	8	13-1/2	5/8	13	11-3/4	11-3/16	13-3/16	16	8	7/8	11-3/4	40 mm	1	3-3/8	287
OF 25	28	1	10	16	3/4	15	16-1/4	12-1/2	14-3/4	20-7/8	12	1	14-1/4	40 mm	1-1/2	4-1/4	463
OF30	48	1-1/2 - 2	12	19	3/4	17-1/2	17-5/8	13-13/16	16	20-7/8	12	1	17	45 mm	1-1/2	5	617
OF 35	82	1-1/2 - 2	14	21	3/4	21	19-3/16	15-3/4	18-1/4	23	12	1-1/8	18-3/4	45 mm	2	5-1/2	904
OF 40	125	1-1/2 - 2	16	23-1/2	1	24	20-7/8	16-3/8	18-7/8	26-7/8	16	1-1/8	21-1/4	45 mm	2	7	1,124
OF 45	196	2 - 3	18	25-1/4	1-5/16	26-1/5	23-5/8	19-1/8	21-7/8	27-3/8	16	1-1/4	22-3/4	55 mm	2	7-3/4	1,576

[1] Standard rpm's: 12.5, 15.5, 18, 21, 25, 31, 35, 42 rpm - other speeds available.

[2] HP is typical and is based on maximum capacity.

Copyright 1998 Bush & Wilton, Inc. - All Rights Reserved

BUSH & WILTON, INC.

P.O. Box 691385 | Charlotte, NC 28227- 7024

Tel: 704.573.6858 | Fax: 704.573.6802

mail@bushandwilton.com

http://www.bushandwilton.com